

Üæcä} *Äc [ÄF€€€XÄÜÜX

Ü * ! * ÄÄ [ç^i] [æäÄtæcä} *Äc [ÄH€€€€ {] ^! ^Ä] ^æ\ÄÄQä^æ|Ä- [iÄ] iä) c^äÄ&äi & ~ äcÄä [æiä

ä) Ää} ^ø] ^) •äç^Ä] ! [ä ~ & cÄÄŠ^æäÄ • [|ä^!æà|^Ä] ^!ÄTÜŠËÜVÖËG€Ä { ^c@ [äÄG€i

		KBPC 25005	KBPC 2501	KBPC 2502	KBPC 2504	KBPC 2506	KBPC 2508	KBPC 2510	UNITS
Maximum recurrent peak reverse voltage	V_{RRM}	50	100	200	400	600	800	1000	V
Maximum RMS voltage	V_{RMS}	35	70	140	280	420	560	700	V
Maximum DC blocking voltage	V_{DC}	50	100	200	400	600	800	1000	V
Maximum average forward Output current @ $T_A=25^\circ\text{C}$	$I_{F(AV)}$	25.0							A
Peak forward surge current 8.3ms single half-sine-wave superimposed on rated load	I_{FSM}	300.0							A
Maximum instantaneous forward voltage @ 12.5 A	V_F	1.1							V
Maximum reverse current @ $T_A=25^\circ\text{C}$ at rated DC blocking voltage @ $T_A=100^\circ\text{C}$	I_R	10.0 1.0							A mA
Operating junction temperature range	T_J	- 55 ---- + 125							$^\circ\text{C}$
Storage temperature range	T_{STG}	- 55 ---- + 150							$^\circ\text{C}$

